

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **272**
Product name: **NORPHEN 200 FUEL (B)**
UFI: **TGQ1-N0PT-P008-5K08**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **EPOXY ENAMEL RESISTANT TO HYDROCARBONS**

1.3. Details of the supplier of the safety data sheet

Name: **NORD RESINE S.p.A.**
Full address: **Via Fornace Vecchia, 79**
District and Country: **31058 Susegana (TV) Italia**
Tel.: **+39 0438-437511**
Fax: **+39 0438-435155**
e-mail address of the competent person responsible for the Safety Data Sheet: **annabreda@nordresine.com**
Supplier: **NORD RESINE S.p.A.**

1.4. Emergency telephone number

For urgent inquiries refer to:

- Ireland**
National Poisons Information Centre
+353 018092166
+353 018092566
- Malta**
Malta Competition and Consumer Affairs Authority (MCCAA)
+356 2395 2000
- Belgium**
Centre Antipoisons: +32 022649636
- Germany**
BfR Bundesinstitut für Risikobewertung: +49 30184120
- Netherlands**
National Poisons Information Center / University Medical Center Utrecht
+31 88 75 585 61
- Croatia**
Croatian Institute of Public Health, Division for Toxicology: +38514686910
- Sveden**
Swedish Poisons Information Centre: +46104566750

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.
Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

SECTION 2. Hazards identification ... / >>

Hazard classification and indication:

Acute toxicity, category 4	H302	Harmful if swallowed.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Precautionary statements:

P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor.
P264	Wash your hands thoroughly with soap and water after use.

Contains:

4,4'-methylenebis(cyclohexylamine)
Formaldehyde, polymeric reaction products with 4-tert-butylphenol, m-phenylenebis(methylamine) and trimethylhexane-1,6-diamine
Trimethylhexamethylenediamine
M-PHENYLENEBIS (METHYLAMINE)
BENZYL ALCOHOL

VOC (Directive 2004/42/EC) :

Two-pack reactive performance coatings for specific end use such as floors.

VOC given in g/litre of product in a ready-to-use condition :

202,95

Limit value:

500,00

- Catalysed with :

200,00 %

NORPHEN 200 FUEL (A)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product contains substances with endocrine disrupting properties in concentration \geq 0,1%:
salicylic acid

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
BENZYL ALCOHOL		
INDEX	603-057-00-5	35 ≤ x < 50
EC	202-859-9	
CAS	100-51-6	
REACH Reg.	01-2119492630-38	
4,4'-methylenebis(cyclohexylamine)		
INDEX		35 ≤ x < 50
EC	217-168-8	
CAS	1761-71-3	
REACH Reg.	01-2119541673-38	
PHENOL, STYRENATED		
INDEX		3 ≤ x < 5
EC	262-975-0	
CAS	61788-44-1	
REACH Reg.	01-2119979575-18	
salicylic acid		
INDEX	607-732-00-5	1 ≤ x < 3
EC	200-712-3	
CAS	69-72-7	
REACH Reg.	01-2119486984-17	
M-PHENYLENEBIS (METHYLAMINE)		
INDEX		1 ≤ x < 3
EC	216-032-5	
CAS	1477-55-0	
REACH Reg.	01-2119480150-50	
Formaldehyde, polymeric reaction products with 4-tert-butylphenol, m-phenylenebis(methylamine) and trimethylhexane-1,6-diamine		
INDEX		1 ≤ x < 3
EC		
CAS		
REACH Reg.	esente	
Trimethylhexamethylenediamine		
INDEX		0,5 ≤ x < 1
EC	247-063-2	
CAS	25513-64-8	
REACH Reg.	01-2119560598-25	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Rinse your mouth with running water. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

SECTION 4. First aid measures ... / >>

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

SECTION 6. Accidental release measures ... / >>

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024
	ACGIH	ACGIH 2025

SECTION 8. Exposure controls/personal protection ... / >>

M-PHENYLENEBIS (METHYLAMINE)

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
			mg/m3	
			ppm	
VLEP	FRA		0,1	
MV	SVN	0,1		
ACGIH			0,018 (C)	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,094	mg/l
Normal value in marine water	0,009	mg/l
Normal value for fresh water sediment	12,4	mg/kg/d
Normal value for marine water sediment	1,24	mg/kg/d
Normal value for marine water, intermittent release	0,152	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	2,44	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		NPI		NPI				
Inhalation	NPI	NPI	NPI	NPI	MED	NPI	0,2	1,2
Skin	NPI	NPI	NPI	NPI	MED	NPI	MED	0,33
								mg/kg bw/d

BENZYL ALCOHOL

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
			mg/m3	
			ppm	
TLV	CZE	40	9	
AGW	DEU	22	5	SKIN 11
MAK	DEU	22	5	SKIN
NDS/NDSch	POL	240		
ПДК	RUS		5	n
MV	SVN	22	5	SKIN
			44	10

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	0,1	mg/l
Normal value for fresh water sediment	5,27	mg/kg
Normal value for marine water sediment	0,527	mg/kg
Normal value for water, intermittent release	2,3	mg/l
Normal value of STP microorganisms	39	mg/l
Normal value for the terrestrial compartment	0,45	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		20		4				
		mg/kg bw/d		mg/kg bw/d				
Inhalation		27		5,4	110		22	
		mg/m3		mg/m3	mg/m3		mg/m3	
Skin		20		4	40		8	
		mg/kg bw/d		mg/kg bw/d	mg/kg bw/d		mg/kg bw/d	

SECTION 8. Exposure controls/personal protection ... / >>

4,4'-methylenebis(cyclohexylamine)

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,08	mg/l
Normal value in marine water	0,008	mg/l
Normal value for fresh water sediment	137	mg/kg/d
Normal value for marine water sediment	13,7	mg/kg
Normal value for water, intermittent release	0,08	mg/l
Normal value of STP microorganisms	3,2	mg/l
Normal value for the terrestrial compartment	27,2	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,06 mg/kg bw/d				
Inhalation				0,21 mg/m3				0,13 mg/m3
Skin								0,1 mg/kg bw/d

salicylic acid

Predicted no-effect concentration - PNEC

Normal value in fresh water	200	µg/L
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	1,42	mg/kg
Normal value for marine water sediment	142	µg/kg
Normal value for marine water, intermittent release	20	µg/L
Normal value of STP microorganisms	162	mg/l
Normal value for the terrestrial compartment	166	µg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4,0 mg/kg		1,0 mg/kg				
Inhalation		NPI	NPI	4,0 mg/m ³	NPI	NPI	5,0 mg/m ³	5,0 mg/m ³
Skin		NPI	NPI	1,0 mg/kg	NPI	NPI	NPI	2,3 mg/kg

Trimethylhexamethylenediamine

Predicted no-effect concentration - PNEC

Normal value in fresh water	102	µg/L
Normal value in marine water	315	µg/L
Normal value for fresh water sediment	622	µg/kg
Normal value for marine water sediment	62	µg/kg
Normal value for marine water, intermittent release	10,2	µg/L
Normal value of STP microorganisms	72	mg/l
Normal value for the terrestrial compartment	10	mg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NEA		50,0 µg/kg				
Inhalation		NEA	NEA	NEA	HIGH	NPI	HIGH	NPI
Skin		NEA	NEA	NEA	HIGH	HIGH	HIGH	HIGH

SECTION 8. Exposure controls/personal protection ... / >>

PHENOL, STYRENATED

Predicted no-effect concentration - PNEC

Normal value in fresh water	4	µg/L
Normal value in marine water	46	µg/L
Normal value for fresh water sediment	248	µg/kg
Normal value for marine water sediment	24,8	µg/kg
Normal value for water, intermittent release	4,6	µg/L
Normal value for marine water, intermittent release	400	ng/l
Normal value of STP microorganisms	36,2	mg/l
Normal value for the terrestrial compartment	47,3	µg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		LOW		750,0 µg/kg				
Inhalation		LOW	LOW	1,31 mg/m³	LOW	LOW	LOW	7,4 mg/m³
Skin		LOW	LOW	750,0 µg/kg	LOW	LOW	LOW	2,1 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Viton or fluoroelastomer (FKM)

Thickness: 0,5 mm

Breakthrough time: 480 min

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellow	
Odour	amino	
Melting point / freezing point	not determined	Reason for missing data: not determined
Initial boiling point	not determined	Reason for missing data: not determined
Flammability	not determined	
Lower explosive limit	not determined	Reason for missing data: not determined
Upper explosive limit	not determined	Reason for missing data: not determined
Flash point	> 93 °C	
Auto-ignition temperature	not determined	Reason for missing data: not determined
Decomposition temperature	not determined	Reason for missing data: not determined
pH	11	
Kinematic viscosity	not determined	Reason for missing data: not determined
Solubility	not determined	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not determined	Reason for missing data: not determined
Density and/or relative density	1,02 kg/l	
Relative vapour density	not determined	Reason for missing data: not determined
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 50,33 % - 513,37 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F. Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron, oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

10.5. Incompatible materials

BENZYL ALCOHOL

SECTION 10. Stability and reactivity ... / >>

Incompatible with: sulphuric acid, oxidising substances, aluminium.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	779,67 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

Corrosive to the respiratory tract.

BENZYL ALCOHOL

LD50 (Dermal):	2000 mg/kg Rabbit
LD50 (Oral):	1200 mg/kg
LC50 (Inhalation vapours):	> 4,1 mg/l/4h Rat

4,4'-methylenebis(cyclohexylamine)

LD50 (Dermal):	2110 mg/kg Rabbit
LD50 (Oral):	625 mg/kg Rat

PHENOL, STYRENATED

LD50 (Dermal):	2000 mg/kg (rat)
LD50 (Oral):	2000 mg/kg (rat)

salicylic acid

LD50 (Dermal):	2000 mg/kg (rat)
LD50 (Oral):	891 mg/kg (rat)

The acute oral toxicity of salicylic acid (purity unknown) was tested in a test similar to OECD guideline 401. Five male Albino rats per group (4 groups) were administered a single dose of the test substance in a corn oil suspension. The dose were 464, 681, 1000 and 1470 mg/kg bw. The animals were then observed for 14 days.

Under the conditions of this test, the LD50 was 891 mg/kg bw. Signs of intoxication were hypoactivity and muscular weakness. At necropsy, no significant findings were observed in survivors, whereas inflammation of the gastrointestinal tract was observed in decedents. Based on the results of this study, salicylic acid would be classified as harmful in male rats by oral route, according to the Directive (67/548/EEC) on dangerous substance.

M-PHENYLENEBIS (METHYLAMINE)

LD50 (Dermal):	> 3100 mg/kg Rat
LD50 (Oral):	930 mg/kg Rat
LC50 (Inhalation mists/powders):	1,34 mg/l/4h Rat

SECTION 11. Toxicological information ... / >>

Trimethylhexamethylenediamine
LD50 (Oral): 910 mg/kg (rat)

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product contains the following endocrine disruptors in concentrations of 0.1% or greater by weight that may have endocrine disrupting effects on humans and cause adverse effects on the exposed individual or his or her progeny:
salicylic acid

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

BENZYL ALCOHOL
LC50 - for Fish 10 mg/l/96h Bluegill

4,4'-methylenebis(cyclohexylamine)
LC50 - for Fish > 100 mg/l/96h Leuciscus idus
EC50 - for Crustacea 6,84 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 140 mg/l/72h
Chronic NOEC for Crustacea 4 mg/l Daphnia magna

PHENOL, STYRENATED
LC50 - for Fish 5,6 mg/l/96h
EC50 - for Crustacea 4,6 mg/l/48h
EC50 - for Algae / Aquatic Plants 1,35 mg/l/72h
Chronic NOEC for Fish > 187,9 µg/L/840h
Chronic NOEC for Crustacea 200 µg/L

SECTION 12. Ecological information ... / >>

salicylic acid	
LC50 - for Fish	1,853 g/L/24h
EC50 - for Crustacea	870 mg/l/48h
EC50 - for Algae / Aquatic Plants	100 mg/l/72h
Chronic NOEC for Crustacea	10 mg/l
M-PHENYLENEBIS (METHYLAMINE)	
LC50 - for Fish	87,6 mg/l/96h <i>Oryzias latipes</i>
EC50 - for Crustacea	15,2 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	20,3 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Trimethylhexamethylenediamine	
LC50 - for Fish	174 mg/l/48h
EC50 - for Algae / Aquatic Plants	43,5 mg/l/72h
EC10 for Crustacea	1,02 mg/L/504h
Chronic NOEC for Fish	10,9 mg/L/720h
Chronic NOEC for Crustacea	1,02 mg/l
Chronic NOEC for Algae / Aquatic Plants	16 mg/l

12.2. Persistence and degradability

BENZYL ALCOHOL	
Rapidly degradable	
PHENOL, STYRENATED	
Solubility in water	1,95 g/l
NOT rapidly degradable	
salicylic acid	
Solubility in water	2,55 g/l
Rapidly degradable	
M-PHENYLENEBIS (METHYLAMINE)	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
Trimethylhexamethylenediamine	
Solubility in water	1 g/l
NOT rapidly degradable	

12.3. Bioaccumulative potential

BENZYL ALCOHOL	
Partition coefficient: n-octanol/water	1,1
PHENOL, STYRENATED	
Partition coefficient: n-octanol/water	3,03
BCF	10395
salicylic acid	
Partition coefficient: n-octanol/water	2,64
M-PHENYLENEBIS (METHYLAMINE)	
Partition coefficient: n-octanol/water	0,18
Trimethylhexamethylenediamine	
Partition coefficient: n-octanol/water	-0,3

12.4. Mobility in soil

PHENOL, STYRENATED	
Partition coefficient: soil/water	584,7

SECTION 12. Ecological information ... / >>

salicylic acid	
Partition coefficient: soil/water	35
Trimethylhexamethylenediamine	
Partition coefficient: soil/water	25

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 2735

14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-methylenebis(cyclohexylamine); M-PHENYLENEBIS (METHYLAMINE))

IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-methylenebis(cyclohexylamine); M-PHENYLENEBIS (METHYLAMINE))

IATA: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-methylenebis(cyclohexylamine); M-PHENYLENEBIS (METHYLAMINE))

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
IMDG: not marine pollutant
IATA: NO

SECTION 16. Other information ... / >>

Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)

SECTION 16. Other information ... / >>

14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 08 / 11 / 12 / 14.