

DECLARATION OF PERFORMANCE NO R002-CPR

1 - Unique product-type identification code: **DRY BETON SUPER**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 998-1**

► Harmonized standard: **EN 998-1:2016**

3 - Intended uses: **Designed renovation rendering/plastering mortar (R) for external and internal use.**

4 - VVCP systems: **4**
4 for reaction to fire

5 - Notified bodies: **No tasks for the notified body**

6 - Declared performance:

Essential features	Performance
Adhesion	$\geq 1 \text{ N/mm}^2$ - FP:A
Water absorption	$\geq 0,3 \text{ kg/m}^2$ dopo 24 h
Permeability to water vapor	$\mu \leq 10$
Thermal conductivity ($\lambda_{10, \text{Dry}}$) (average tabulated value; P=50%)	0,29 W/(m·K)
Durability	NPD
Reaction to fire (Euroclass)	A1
Dangerous substances	NPD

Reaction to fire class declared according to the Decision of the Commission 96/603/EC and following amendments.

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)