



BETONSEAL PRIMER


Adhesion promoter for
BETONSEAL MS sealants




TECHNICAL FEATURES



FIELD OF APPLICATION



APPLICATIONS



Description

BETONSEAL PRIMER is a mono-component liquid product that, when applied in small quantities to non-absorbent surfaces of varying nature and shape, leaves a transparent and invisible layer – after the solvent evaporates – that modifies its chemical behaviour and sign. In particular, BETONSEAL PRIMER promotes adhesion in conditions of high humidity, temporary immersion in water and strong temperature ranges.

Field of application

BETONSEAL PRIMER is expressly designed for pre-sealing treatment of:

- Metal surfaces.
- Painted surfaces.
- Some plastics.

For more information see the selection table in the Technical Data Sheet of BETONSEAL MS 2.0.

General preparation of the laying surface

- Clean and dry the surfaces on which you intend to operate.
- Remove dust and detached parts.
- In the case of greasy, oily surfaces or surfaces polluted by release agents, clean them with a pad soaked in BETONSEAL CLEANER (solvent-based degreaser, see Technical Data Sheet).

Product preparation

- Shake the product in the container before picking.
- Avoid spilling any leftover product into the original container.

Product application

BETONSEAL PRIMER is ready to use.

- Pour the amount of product strictly necessary for the operation into a well-cleaned serving container.
- Use within 30 minutes.
- BETONSEAL PRIMER is applicable in one of three ways:
 - with a pad (clean rag or paper).
 - with a brush.
 - with a short-pile roller.

BETONSEAL PRIMER

- For pad applications, the product also exerts a cleaning action on the surfaces on which it is applied.
- In all cases, do not allow product to stagnate on the treated surface.
- Wait for the drying time (about 5 minutes).
- Proceed with the application of BETONSEAL MS sealant.

The best result (from the point of view of adhesion) is obtained by applying sealant within 6 hours after applying the primer.

Consumption

type of application	minimum consumption	maximum consumption	u.m.	notes
On non-absorbent surfaces	20	30	mL/m ²	-

Tool cleaning

- Fresh and dry product: cleaning with ACETONE, nitro thinner or alcohol.

Useful tips for laying

- To obtain the best result, do not exceed the consumption indicated in this Technical Data Sheet.
 - The product is sensitive to moisture.
- Close the package immediately after picking.
- Do not dump any leftover product in the original container.
 - Do not mix with water.
 - Do not dilute with alcohol or acetone.
 - The product is flammable.
 - When applied in poorly aerated areas, it is advisable to adequately ventilate the environment and protect the airways wearing a dust mask equipped with a type A filter (brown strip, against organic vapour) or a type ABEK combined filter (brown-yellow-grey-green strip), according to EN 141.
 - Read the Safety Data Sheet carefully before use.

Technical Data

► PRODUCT IDENTIFICATION DATA		value
Density at 23°C, EN ISO 2811-1	kg/L	0,90 ± 0,01
Brookfield apparent dynamic viscosity (23°C / 50% RH; spindle ASTM#1, 150 rpm), EN ISO 2555	mPa·s	40 ± 10
► APPLICATION DATA AND FINAL PERFORMANCE		value
Surface drying time (23°C, 50%RH), EN ISO 9117-3	Min	5,0 ± 0,5
Application temperature	°C	from +5 to + 35
Ideal time interval for sealing with BETONSEAL MS 2.0	Hours	< 6

Product storage

- 6 months in the original packaging closed, in a dry, covered environment, protected from sunlight and at a temperature between +5°C and +25°C.
- Storage at temperatures above 25°C for long periods shortens the shelf life of the product.

Packaging

VARIANT	PACKAGE	ADR	PACKAGE / PALLET	COMPONENTS	NOTES
-	tin can - 0.5 L	P*	-	-	-

ADR legend:

NO = NON-DANGEROUS goods

P* = DANGEROUS goods packed in limited quantities (packed as per ADR Chapter 3.4)

BETONSEAL PRIMER

Si = DANGEROUS Goods

LEGAL NOTES

The information contained in this Technical Data Sheet is based on the knowledge and experience gained by Nord Resine up to the date of its issue and is for indicative purposes only. It does not constitute a technical specification nor does it imply the assumption of any warranty, express or implied, or liability regarding the results obtainable, which depend on multiple factors beyond the control of Nord Resine.

It is the user's responsibility to verify in advance, also through suitable tests, the suitability of the product for the intended use, compatibility with the substrate, appropriate environmental application conditions, and the execution of the installation according to workmanship standards, assuming all liability arising from the use of the product and the final result of the works.

Nord Resine reserves the right to modify, at any time and without prior notice, product characteristics, packaging, contained quantities, and this technical documentation. Nord Resine products are intended exclusively for professional use.

This Technical Data Sheet cancels and replaces previous editions. Please check the latest and most updated revision at <https://nordresine.com/en/>

EDITION

Issue: 03.01.2008

Revision: 29.01.2018