



**SECTION 2. Hazards identification ... / >>**

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

<b>H341</b>	Suspected of causing genetic defects.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction.

Precautionary statements:

<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.
<b>P273</b>	Avoid release to the environment.
<b>P391</b>	Collect spillage.
<b>P261</b>	Avoid breathing dust.
<b>P201</b>	Obtain special instructions before use.
<b>P308+P313</b>	IF exposed or concerned: Get medical advice / attention.

**Contains:** 2,3-epoxypropyl o-tolyl ether  
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane  
bis-[4-(2,3-epoxipropoxy)phenyl]propane  
Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and  
[2-{{2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl}oxirane and  
[2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

VOC (Directive 2004/42/EC) :

Two-pack reactive performance coatings for specific end use such as floors.

VOC given in g/litre of product in a ready-to-use condition :

335,97

Limit value:

500,00

- Catalysed with :

50,00 %

NORPHEN 200 HCR RESISTENTE AL VINO (B)

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

**SECTION 3. Composition/information on ingredients**

**SECTION 3. Composition/information on ingredients** ... / >>

**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>bis-[4-(2,3-epoxipropoxy)phenyl]propane</b>		
INDEX	603-073-00-2 35 ≤ x < 50	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC	216-823-5	Skin Irrit. 2 H315: ≥ 5%, Eye Irrit. 2 H319: ≥ 5%
CAS	1675-54-3	
REACH Reg.	01-2119456619-26	
<b>2,3-epoxypropyl o-tolyl ether</b>		
INDEX	603-056-00-X 35 ≤ x < 50	Muta. 2 H341, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: C
EC	218-645-3	
CAS	2210-79-9	
REACH Reg.	01-2119966907-18	
<b>Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane</b>		
INDEX	3 ≤ x < 5	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412
EC	618-939-5	
CAS	933999-84-9	
REACH Reg.	01-2119463471-41	
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
INDEX	607-195-00-7 1 ≤ x < 3	Flam. Liq. 3 H226, STOT SE 3 H336
EC	203-603-9	
CAS	108-65-6	
REACH Reg.	01-2119475791-29	
<b>Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane</b>		
INDEX	0,1 ≤ x < 0,5	Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Chronic 2 H411
EC	701-263-0	
CAS	9003-36-5	
REACH Reg.	01-2119454392-40	
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
INDEX	601-022-00-9 0,1 ≤ x < 0,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
EC	215-535-7	
CAS	1330-20-7	
REACH Reg.	01-2119488216-32	
<b>ETHYLBENZENE</b>		
INDEX	601-023-00-4 0 < x < 0,1	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412 LC50 Inhalation vapours: 17,2 mg/l/4h
EC	202-849-4	
CAS	100-41-4	
REACH Reg.	01-2119489370-35	
<b>Quartz</b>		
INDEX	0 < x < 0,01	STOT RE 1 H372
EC	238-878-4	
CAS	14808-60-7	
REACH Reg.	01-2119471310-51	
<b>TOLUENE</b>		
INDEX	601-021-00-3 0 < x < 0,01	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC	203-625-9	
CAS	108-88-3	
REACH Reg.	01-2119471310-51	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures**

**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15

### SECTION 4. First aid measures ... / >>

minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

**INGESTION:** Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

**INHALATION:** Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

**DELAYED EFFECTS:** Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice / attention.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

#### Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

### SECTION 6. Accidental release measures ... / >>

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

2-METHOXY-1-METHYLETHYL ACETATE

Store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"

**SECTION 8. Exposure controls/personal protection** ... / >>

SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2025

**2,3-epoxypropyl o-tolyl ether**

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,0028	mg/l
Normal value in marine water	0,00028	mg/l
Normal value for fresh water sediment	0,039	mg/kg/d
Normal value for marine water sediment	0,0039	mg/kg/d
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,012	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,14 mg/kg bw/d				
Inhalation					40 mg/m3	40 mg/m3	0,46 mg/m3	0,46 mg/m3
Skin								0,139 mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>**

**2-METHOXY-1-METHYLETHYL ACETATE**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	270	49,14	550	100,1	SKIN
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
TLV	GRC	275	50	550	100	
AK	HUN	275	50	550	100	
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN Allegato XXXVIII D.Lgs. 81/08
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
ПДК	RUS			10		n
MV	SVN	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,0635	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value for water, intermittent release	6,35	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				36 mg/kg/d				
Inhalation				33 mg/m3			NPI	275 mg/m3
Skin			NPI	320 mg/kg/d			NPI	796 mg/kg/d

**Quartz**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP Allegato XXXVIII D. Lgs. 81/08
TGG	NLD	0,075				RESP
VLE	PRT	0,025				RESP
NDS/NDSch	POL	0,1				RESP
TLV	ROU	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

**SECTION 8. Exposure controls/personal protection ... / >>**

**TOLUENE**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	192	50,112	384	100,224	SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	380	100	SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
TLV	GRC	192	50	384	100	
AK	HUN	192	50	384	100	SKIN
GVI/KGVI	HRV	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN Allegato XXXVIII D.Lgs. 81/08
TGG	NLD	150		384		
VLE	PRT	192	50	384	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	192	50	384	100	SKIN
ПДК	RUS	50		150		n
MV	SVN	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,68	mg/l
Normal value in marine water	0,68	mg/l
Normal value for fresh water sediment	16,39	mg/kg/d
Normal value for marine water sediment	16,39	mg/kg/d
Normal value of STP microorganisms	13,61	mg/l
Normal value for the terrestrial compartment	2,89	mg/kg/d

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	226	226	56,5	56,5	384	384	192	192
	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3
Skin	LOW	NPI	NPI	226	LOW	NPI	NPI	384
				mg/kg bw/d				mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>**

**ETHYLBENZENE**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
AK	HUN	442	100	884	200	SKIN
GVI/KGVI	HRV	442	100	884	200	SKIN
VLEP	ITA	442	100	884	200	SKIN Allegato XXXVIII D.Lgs. 81/08
TGG	NLD	215		430		SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
TLV	ROU	442	100	884	200	SKIN
ПДК	RUS	50		150		n
MV	SVN	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	13,7	mg/kg/d
Normal value for marine water sediment	1,37	mg/kg/d
Normal value for marine water, intermittent release	0,1	mg/l
Normal value of STP microorganisms	9,6	mg/l
Normal value for the food chain (secondary poisoning)	20	mg/kg
Normal value for the terrestrial compartment	2,68	mg/kg/d

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		1,6 mg/kg bw/d				
Inhalation	LOW	LOW	LOW	15 mg/m3	293 mg/m3	LOW	442 mg/m3	77 mg/m3
Skin	NPI	NPI	NPI	NPI	NPI	NPI	NPI	180 mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>**

**XYLENE (MIXTURE OF ISOMERS)**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	46	400	92	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN Allegato XXXVIII D.Lgs. 81/08
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSch	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value for water, intermittent release	0,327	mg/l
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								1,6 mg/kg/d
Inhalation				14,8 mg/m3	289 mg/m3	289 mg/m3		77 mg/m3
Skin				108 mg/kg/d				180 mg/kg/d

**Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane**

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,003	mg/l
Normal value for fresh water sediment	0,294	mg/kg
Normal value for marine water sediment	0,029	mg/kg
Normal value for water, intermittent release	0,025	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,237	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				6,25 mg/kg bw/d				
Inhalation				8,7 mg/m3				29,39 mg/m3
Skin				62,5 mg/kg bw/d	0,0083 mg/cm2			104,15 mg/kg bw/d

**SECTION 8. Exposure controls/personal protection** ... / >>

**Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane**

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,0115	mg/l
Normal value in marine water	0,00115	mg/l
Normal value for fresh water sediment	0,283	mg/kg
Normal value for marine water sediment	0,0283	mg/kg
Normal value for water, intermittent release	0,115	mg/l
Normal value of STP microorganisms	1	mg/l
Normal value for the terrestrial compartment	0,223	mg/kg/d

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,83 mg/kg bw/d				0,83 mg/kg bw/d		
Inhalation		2,9 mg/m3	0,27 mg/m3	2,9 mg/m3		4,9 mg/m3	0,44 mg/m3	4,9 mg/m3
Skin	0,0136 mg/kg bw/d	1,7 mg/kg bw/d	0,0136 mg/cm2	1,7 mg/kg bw/d	0,0136 mg/kg bw/d		0,0226 mg/cm2	2,8 mg/kg bw/d

**bis-[4-(2,3-epoxipropoxy)phenyl]propane**

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,006	mg/l
Normal value in marine water	0,0006	mg/l
Normal value for fresh water sediment	0,996	mg/kg
Normal value for marine water sediment	0,0996	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,75 mg/kg/d				
Inhalation							VND	12,25 mg/m3
Skin			VND	3,571 mg/kg/d			VND	8,33 mg/kg

**Legend:**

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Butyl rubber (IIR)

Thickness: 0,35 mm

Breakthrough time: 480 min

Material: Nitrile rubber (NBR)

Thickness: 0,5 mm

Breakthrough time: 480 min

**SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### SECTION 8. Exposure controls/personal protection ... / >>

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

#### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	dark red	
Odour	characteristic	
Melting point / freezing point	not determined	Reason for missing data: not determined
Initial boiling point	not determined	Reason for missing data: not determined
Flammability	not determined	
Lower explosive limit	not determined	Reason for missing data: not determined
Upper explosive limit	not determined	Reason for missing data: not determined
Flash point	> 100 °C	
Auto-ignition temperature	not determined	Reason for missing data: not determined
Decomposition temperature	not determined	Reason for missing data: not determined
pH	not applicable	
Kinematic viscosity	not determined	Reason for missing data: not determined
Solubility	soluble in organic solvents	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not determined	Reason for missing data: not determined
Density and/or relative density	1,23 kg/l	Method: EN ISO 1675 Temperature: 23 °C
Relative vapour density	not determined	Reason for missing data: not determined
Particle characteristics	not applicable	

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 1,77 % - 21,74 g/litre

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### 2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

##### TOLUENE

Avoid exposure to: light.

## SECTION 10. Stability and reactivity ... / >>

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

#### TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

#### ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

#### XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials

#### 2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

#### ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Metabolism, toxicokinetics, mechanism of action and other information

##### 2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

#### Information on likely routes of exposure

##### 2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

##### TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

##### ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

##### XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of environmental air.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**SECTION 11. Toxicological information ... / >>**

**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

**TOLUENE**

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

**ETHYLBENZENE**

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesi). Is irritating for skin, conjunctiva and respiratory tract.

**XYLENE (MIXTURE OF ISOMERS)**

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

**XYLENE (MIXTURE OF ISOMERS)**

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

**2,3-epoxypropyl o-tolyl ether**

LD50 (Dermal):	2000 mg/kg Rabbit
LC50 (Inhalation vapours):	1220 mg/l

**2-METHOXY-1-METHYLETHYL ACETATE**

LD50 (Dermal):	2000 mg/kg Rat
LD50 (Oral):	6190 mg/kg Rat

**TOLUENE**

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

**ETHYLBENZENE**

LD50 (Dermal):	15400 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

**XYLENE (MIXTURE OF ISOMERS)**

LD50 (Dermal):	4350 mg/kg Rabbit
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat

**Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and**

<b>[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane</b>	
LD50 (Dermal):	> 2000 mg/kg Rat
LD50 (Oral):	> 5000 mg/kg Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

**SECTION 11. Toxicological information ... / >>**

**2-METHOXY-1-METHYLETHYL ACETATE**

Species: rabbit  
Result: non-irritating  
Method: OECD 404

**XYLENE (MIXTURE OF ISOMERS)**

Causes irritation (redness, burning sensation), dryness and slight flaking of the skin

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane  
The skin irritation of bisphenol F diglycidyl ether was determined to be mild to non-irritating based on the six Klimisch 1 and 2 studies conducted according to OECD guidelines.

In the experimental conditions used, only one product induced erythema and edema reactions above the significance threshold (score 2 for erythema or edema) and was classified as irritant according to EEC directive no. 83/467/1983. The other studies indicated mild irritation, but not sufficient to reach the classification threshold.

Two repeated dose cumulative irritation studies were performed and under the experimental conditions employed the test materials induced significant irritation after repeated application and a potential for cumulative skin irritation was found in albino rabbits. Effects on skin irritation/corrosion: slightly irritating.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

**2-METHOXY-1-METHYLETHYL ACETATE**

Species: rabbit  
Result: non-irritating  
Method: OECD 405

**XYLENE (MIXTURE OF ISOMERS)**

Irritating to eyes

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane  
The ocular irritation of bisphenol F diglycidyl ether was determined to be non-irritating based on the four Klimisch 1 and 2 studies conducted according to OECD guidelines. In rabbit eye irritation tests, 0.1 ml of the test material caused no irritation and no initial pain response.

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

**2-METHOXY-1-METHYLETHYL ACETATE**

Species: guinea pig  
Result: non-sensitizing  
Method: OECD 406

Skin sensitization

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane  
Bisphenol F diglycidyl ether (BPFDE) tested positive for induction of skin sensitization in the mouse Local Lymph Node Assay (LLNA). Based on an EC3 value of 0.7%, BPFDE is considered a strong skin sensitizer. According to ECHA guidelines, this EC3 value was converted to an EC3 value of 175 ug/cm2 and is considered the LOAEL for the induction of skin sensitization in the LLNA mouse for BPFDE. From sensitization tests it can be concluded that BPFDE is a sensitizer.

GERM CELL MUTAGENICITY

Suspected of causing genetic defects

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

**TOLUENE**

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

## SECTION 11. Toxicological information ... / >>

### ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).  
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

### XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

### Target organs

#### ETHYLBENZENE

Test: STOT RE - Route: Inhalation. Auditory system, ears

#### XYLENE (MIXTURE OF ISOMERS)

May cause damage to organs (respiratory tract) through prolonged or repeated exposure.

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

### 12.1. Toxicity

#### 2,3-epoxypropyl o-tolyl ether

LC50 - for Fish	7,5 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	3,3 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	5,1 mg/l/72h Selenastrum capricornutum

#### 2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish	> 100 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	500 mg/l/48h Daphnia magna
Chronic NOEC for Crustacea	100 mg/l Daphnia magna

#### TOLUENE

LC50 - for Fish	5,5 mg/l/96h
EC50 - for Crustacea	3,78 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 134 mg/l/72h

#### Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and

[2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50 - for Fish	2,54 mg/l/96h
EC50 - for Crustacea	2,55 mg/l/48h Daphnia Magna
EC50 - for Algae / Aquatic Plants	1,8 mg/l/72h

**SECTION 12. Ecological information** ... / >>

bis-[4-(2,3-epoxipropoxi)phenyl]propane  
LC50 - for Fish 1,5 mg/l/96h Fish

**12.2. Persistence and degradability**

2-METHOXY-1-METHYLETHYL ACETATE  
Solubility in water > 10000 mg/l  
Rapidly degradable 83% (28 d. OECD 301 F)

TOLUENE  
Solubility in water 100 - 1000 mg/l  
Rapidly degradable

ETHYLBENZENE  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)  
Solubility in water 100 - 1000 mg/l  
Degradability: information not available

bis-[4-(2,3-epoxipropoxi)phenyl]propane  
Solubility in water 0,1 - 100 mg/l  
NOT rapidly degradable

**12.3. Bioaccumulative potential**

2,3-epoxypropyl o-tolyl ether  
Partition coefficient: n-octanol/water 2,16

2-METHOXY-1-METHYLETHYL ACETATE  
Partition coefficient: n-octanol/water 1,2 Log Kow 20°C - OECD 117

TOLUENE  
Partition coefficient: n-octanol/water 2,73  
BCF 90

ETHYLBENZENE  
Partition coefficient: n-octanol/water 3,6

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: n-octanol/water 3,12  
BCF 25,9

bis-[4-(2,3-epoxipropoxi)phenyl]propane  
Partition coefficient: n-octanol/water > 2,918  
BCF 31

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

### 14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane; 2,3-epoxypropyl o-tolyl ether)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane; 2,3-epoxypropyl o-tolyl ether)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane; 2,3-epoxypropyl o-tolyl ether)

### 14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



### 14.4. Packing group

ADR / RID, IMDG, IATA: III



### SECTION 15. Regulatory information ... / >>

2-METHOXY-1-METHYLETHYL ACETATE  
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane  
bis-[4-(2,3-epoxipropoxy)phenyl]propane

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Muta. 2</b>	Germ cell mutagenicity, category 2
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H341</b>	Suspected of causing genetic defects.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH205</b>	Contains epoxy constituents. May produce an allergic reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit

### SECTION 16. Other information ... / >>

- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.