

DECLARATION OF PERFORMANCE NO R018-CPR

1 - Unique product-type identification code: **GROVE 00 NHL INJECTION**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 998-2**

► **Harmonized standard: EN 998-2:2016**

3 - Intended uses: **Designed, general purpose masonry mortar (G, M15) for use on walls, columns and partitions .**

4 - VVCP systems: **2+**
4 for reaction to fire

5 - Notified bodies: **ICMQ SPA N. 1305**

6 - Declared performance:

Essential features	Performance
Compressive strength	M15
Shear bond strength	0.15 N/mm ² (tabulated value)
Chloride ion content	0,003 %
Water absorption	0,025 kg/(m ² min ^{0,5})
Permeability to water vapor	μ =10/35 (tabulated value)
Thermal conductivity (λ10,dry) (tabulated value; P=50%)	1,17 W/(m·K)
Durability	NPD
Reaction to fire (Euroclass)	A1
Dangerous substances	NPD

Reaction to fire class declared without the need for testing according to the Decision of the Commission 96/603/EC and following amendments.

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)