

# SOLVLINE 100

former SOLVENTE PER NORDCHLOR

Aromatic hydrocarbon solvent



## TECHNICAL FEATURES



SLOW CURING

## Description

SOLVLINE 100 is an anhydrous, stabilized aromatic hydrocarbon (C9) solvent indicated as a thinner and surface cleaner.

## Colour

SOLVLINE 100 is a clear, colorless liquid with a characteristic odor.

## Field of application

SOLVLINE 100 is used as:

- solvent for diluting NORDCHLOR and other products requiring an aromatic hydrocarbon solvent (e.g. chlorinated rubber paint).

## Advantages

- SOLVLINE 100 has a water content of less than 0.1% which makes it suitable for the dilution of chlorinated rubber-based products.
- SOLVLINE 100 has an aromatic hydrocarbon content of >98% with a benzene content of less than 10 ppm.

## Tool cleaning

- SOLVLINE 100 is suitable for cleaning brushes, rollers and spraying equipment for NORDCHLOR series products or other aromatic naphtha-based products.
- SOLVLINE 100 is not suitable for removing residues of turpentine-based products (wood impregnators, solvent-based waxes, etc.)

## Useful tips for laying

- The product is FLAMMABLE.
- Read the Safety Data Sheet carefully before use.

## Technical Data

| ► PRODUCT IDENTIFICATION DATA         |      | value                    |
|---------------------------------------|------|--------------------------|
| Density at 23°C, EN ISO 2811-1        | kg/L | 0,868 ± 0,004            |
| Appearance                            | -    | Clear transparent liquid |
| Odor                                  | -    | Characteristic           |
| Water content (Karl Fischer), ISO 760 | -    | < 0,1%                   |
| Benzene content (GC/MS method)        | ppm  | < 10                     |

# SOLVLINE 100

## Product storage

- 24 months in the closed original packaging, in a dry and covered place away from direct sunlight, at a temperature between +5°C and +30°C.

## Packaging

| VARIANT | PACKAGE           | ADR | PACKAGE / PALLET | COMPONENTS | NOTES |
|---------|-------------------|-----|------------------|------------|-------|
| -       | 12 x 1L cans      | P*  | 32 boxes         |            | -     |
| -       | 4 x 5 L cans      | P*  | 18 boxes         |            | -     |
| -       | steel pail - 20 L | SI' | 33 buckets       |            | -     |

### ADR legend:

NO = NON-DANGEROUS goods

P\* = DANGEROUS goods packed in limited quantities (packed as per ADR Chapter 3.4)

SI = DANGEROUS Goods

## LEGAL NOTES

The information contained in this Technical Data Sheet is based on the knowledge and experience gained by Nord Resine up to the date of its issue and is for indicative purposes only. It does not constitute a technical specification nor does it imply the assumption of any warranty, express or implied, or liability regarding the results obtainable, which depend on multiple factors beyond the control of Nord Resine.

It is the user's responsibility to verify in advance, also through suitable tests, the suitability of the product for the intended use, compatibility with the substrate, appropriate environmental application conditions, and the execution of the installation according to workmanship standards, assuming all liability arising from the use of the product and the final result of the works.

Nord Resine reserves the right to modify, at any time and without prior notice, product characteristics, packaging, contained quantities, and this technical documentation. Nord Resine products are intended exclusively for professional use.

This Technical Data Sheet cancels and replaces previous editions. Please check the latest and most updated revision at <https://nordresine.com/en/>

## EDITION

Issue: 14.01.2026

Revision: -