

DECLARATION OF PERFORMANCE NO RC010- CPR

1 - Unique product-type identification code: **X-POWDER**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 1504-2**

► Harmonized standard: **EN 1504-2:2004**

3 - Intended uses: **Coating for concrete surface protection by moisture control and increasing resistivity**

4 - VVCP systems: **2+**
4 for reaction to fire

5 - Notified bodies: **ICMQ SPA N. 1305**

6 - Declared performance:

Essential features	Performance
Permeability to water vapor	Class I
Capillary absorption and water permeability	$w < 0,1 \text{ kg}/(\text{m}^2 \cdot \text{h}^{0,5})$
Pull-off adhesion	$\geq 2 \text{ N}/\text{mm}^2$
Reaction to fire (Euroclass)	F
Dangerous substances	NPD

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)