

DECLARATION OF PERFORMANCE NO RC031-CPR

1 - Unique product-type identification code: **TRAFFIDECK FLEX 3000 HA**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 1504-2**

► Harmonized standard: **EN 1504-2:2004**

3 - Intended uses: **Coating for surface protection of concrete by protection against penetration hazards, moisture control and increased resistivity**

4 - VVCP systems: **2+**
4 for reaction to fire

5 - Notified bodies: **ICMQ SPA N. 1305**


6 - Declared performance:

Essential features	Performance
CO ₂ permeability	S _D > 50 m
Permeability to water vapor	Class I
Capillary absorption and water permeability	w < 0,1 kg/(m ² · h ^{0,5})
Direct drive adhesion	≥ 1.5 N/mm ² (with primer)
Resistance to cracking (at 23°C)	- Static method: class A5 - Dynamic method: class B4.2
Reaction to fire (Euroclass)	NPD
Dangerous substances	NPD

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)