

DECLARATION OF PERFORMANCE NO C016-CPR

1 - Unique product-type identification code: **EPOSEAL W**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 12004**

► Harmonized standard: **EN 12004: 2007 + A1 2012**

3 - Intended uses: **R2T high-performance reactive adhesive for bonding on interior and exterior floors and walls**

4 - VVCP systems: **SYSTEM 3**
SYSTEM 4 for reaction to fire

5 - Notified bodies: **ELLETIPI N. 1308**

6 - Declared performance:

Essential features	Performance
Adhesion strength:	
Initial tensile adhesion	≥ 2 N/mm ²
Durability:	
Shear adhesion after thermal shock	≥ 2 N/mm ²
Shear adhesion after immersion in water	≥ 2 N/mm ²
Reaction to fire (Euroclass)	E WFT
Release of dangerous substances	NPD

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)