

DECLARATION OF PERFORMANCE NO R008-CPR

1 - Unique product-type identification code: **RASACOLL**

2 - Manufacturer: **NORD RESINE S.p.A. - Via Fornace Vecchia, 79 - I-31058 Susegana (TV)**

This Declaration of Performance describes the performance of the construction product in relation to the essential characteristics of that product, in accordance with the relevant harmonised standards or European Technical Assessments (ETAs):

• **EN 998-1**

► **Harmonized standard: EN 998-1:2016**

3 - Intended uses: **Designed general purpose rendering/plastering mortar (GP) for external and internal use on walls, ceilings, columns and partitions**

4 - VVCP systems: **4**
4 for reaction to fire

5 - Notified bodies: **No tasks for the notified body**

6 - Declared performance:

Essential features	Performance
Reaction to fire (Euroclass)	A2-s1,d0
Adhesion	≥0,2 N/mm ² - FP:B
Water absorption	W _{C2}
Permeability to water vapor	μ ≤ 40
Thermal conductivity (λ _{10,Dry}) (average tabulated value; P=50%)	0,67 W/(m·K)
Durability	NPD
Dangerous substances	NPD

Reaction to fire class declared without the need for testing according to the Commission Delegated Regulation (EU) 2017/1228.

Organic content ≤ 2,5% by weight

Wet products mass per unit area ≤ 6,0 kg/m²

The performance of the product identified above is in accordance with the declared set of performances. This declaration of liability is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lionello Caregnato
(Delegate Councilor)



[NORD RESINE S.p.A. makes DoPs available in PDF format on its website.](#)