

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **161**  
Product name: **W3/W3 IMPERMEABILIZZANTE (C) GRIGIO**  
UFI: **YGC2-K0HA-100K-93S9**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **TRICOMPONENT EPOXY COATING.**

#### 1.3. Details of the supplier of the safety data sheet

Name: **NORD RESINE S.p.A.**  
Full address: **Via Fornace Vecchia, 79**  
District and Country: **31058 Susegana (TV) Italia**  
Tel.: **+39 0438-437511**  
Fax: **+39 0438-435155**  
e-mail address of the competent person responsible for the Safety Data Sheet: **annabreda@nordresine.com**  
Supplier: **NORD RESINE S.p.A.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to:

**Ireland**  
National Poisons Information Centre  
+353 018092166  
+353 018092566

**Malta**  
Malta Competition and Consumer Affairs Authority (MCCAA)  
+356 2395 2000

**Belgium**  
Centre Antipoisons: +32 022649636

**Germany**  
BfR Bundesinstitut für Risikobewertung: +49 30184120

**Netherlands**  
National Poisons Information Center / University Medical Center Utrecht  
+31 88 75 585 61

**Croatia**  
Croatian Institute of Public Health, Division for Toxicology: +38514686910

**Sveden**  
Swedish Poisons Information Centre: +46104566750

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## SECTION 2. Hazards identification ... / >>

### Hazard classification and indication:

Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.

Precautionary statements:

<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P280</b>	Wear protective gloves / eye protection / face protection.
<b>P310</b>	Immediately call a POISON CENTER / doctor.
<b>P261</b>	Avoid breathing dust.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.
<b>P362+P364</b>	Take off contaminated clothing and wash it before reuse.

**Contains:** Quartz (Respirable Crystalline Silica)  
PORTLAND CEMENT  
FLUE DUST

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>PORTLAND CEMENT</b>		
<i>INDEX</i>	$35 \leq x < 50$	<b>Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317</b>
<i>EC</i>	266-043-4	
<i>CAS</i>	65997-15-1	

### SECTION 3. Composition/information on ingredients ... / >>

**Quartz (Respirable Crystalline Silica)**

INDEX  $3 \leq x < 5$  STOT RE 1 H372
EC 238-878-4CAS 14808-60-7
**FLUE DUST**

INDEX  $1 \leq x < 3$  Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317
EC 270-659-9CAS 68475-76-3REACH Reg. 01-2119486767-17

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

**EYES:** Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

**INGESTION:** Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

**INHALATION:** Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

**DELAYED EFFECTS:** Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment: see section 4.1

#### Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

## SECTION 5. Firefighting measures ... / >>

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory references:

ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
HRV	Hrvatska	PRAVILNIK O IZMJENAMA I DOPUNAMA PRAVILNIKA O ZAŠTITI RADNIKA OD IZLOŽENOSTI OPASNIM KEMIKALIJAMA NA RADU, GRANIČNIM VRIJEDNOSTIMA IZLOŽENOSTI I BILOŠKIM GRANIČNIM VRIJEDNOSTIMA
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei 2024, nr. 2024-0000092805, tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2022/431
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a

### SECTION 8. Exposure controls/personal protection ... / >>

POL	Polska	Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a agentes cancerígenos ou mutagénicos e procede à quarta alteração
ROU	România	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVN	Slovenija	HOTĂRĂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca
EU	OEL EU	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024
	ACGIH	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2025

#### Quartz (Respirable Crystalline Silica)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP Allegato XXXVIII D. Lgs. 81/08
TGG	NLD	0,075				RESP
VLE	PRT	0,05				RESP
NDS/NDSch	POL	0,1				RESP
TLV	ROU	0,1				RESP
MV	SVN	0,05				RESP
OEL	EU	0,1				RESP
ACGIH		0,025				RESP

#### PORTLAND CEMENT

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
ACGIH		1				RESP

#### FLUE DUST

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	282	µg/L
Normal value in marine water	282	µg/L
Normal value for fresh water sediment	875	µg/kg
Normal value for marine water sediment	88	µg/kg
Normal value for marine water, intermittent release	28	µg/L
Normal value of STP microorganisms	6	mg/l
Normal value for the terrestrial compartment	5	mg/kg
Normal value for the atmosphere	NPI	

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		LOW		LOW				
Inhalation		NPI	840,0 µg/m³	NPI	4,0 mg/m³	NPI	840,0 µg/m³	NPI
Skin		LOW	LOW	LOW	LOW	LOW	LOW	LOW

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for particulate not otherwise classified (PNO) respirable fraction: 3 mg/m3; PNO inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment. The above values are not TLVs, but guide

## SECTION 8. Exposure controls/personal protection ... / >>

values, to be used for particles that do not have their own TLV and that are insoluble or poorly soluble in water and have low toxicity.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR)

Thickness: 0,35 mm

Breakthrough time: 480 min

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

#### RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	powder	
Colour	grey	
Odour	odourless	
Melting point / freezing point	not determined	Reason for missing data: not determined
Initial boiling point	not applicable	
Flammability	not applicable	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	not applicable	
Auto-ignition temperature	not applicable	
Decomposition temperature	not applicable	
pH	not determined	Reason for missing data: not determined
Kinematic viscosity	not applicable	
Solubility	slightly soluble	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not applicable	
Density and/or relative density	1,47 kg/l	Method: EN 1097-3
Relative vapour density	not applicable	
Particle characteristics	not available	

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

#### Flammable liquids

Sustained combustibility does not sustain combustion

**SECTION 9. Physical and chemical properties ... / >>**

9.2.2. Other safety characteristics

Oxidising properties not applicable

**SECTION 10. Stability and reactivity**

**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**PORTLAND CEMENT**

Wet cement is alkaline and incompatible with acids, ammonium salts, aluminum and other non-noble metals.

Cement, in contact with hydrofluoric acid, decomposes producing corrosive silicon tetrafluoride gas.

Cement reacts with water and forms silicates and calcium hydroxide. Silicates react with powerful oxidants such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride and oxygen bifluoride.

**10.3. Possibility of hazardous reactions**

The powders are potentially explosive when mixed with air.

**10.4. Conditions to avoid**

Avoid environmental dust build-up.

**10.5. Incompatible materials**

**PORTLAND CEMENT**

Wet cement is alkaline and incompatible with acids, ammonium salts, aluminum and other non-noble metals.

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

**SECTION 11. Toxicological information ... / >>**

FLUE DUST  
LD50 (Dermal): 2000 mg/kg (rat)  
LD50 (Oral): 1848 mg/kg (rat)  
LC50 (Inhalation mists/powders): 6,04 mg/L/4/h (rat)

SKIN CORROSION / IRRITATION

Causes skin irritation

**PORTLAND CEMENT**

Cement in contact with moist skin can cause thickening, cracking and splitting of the skin. Prolonged contact in combination with existing abrasions can cause severe burns.  
Some individuals may develop eczema following exposure to moist cement dust, caused by the high pH which can induce irritant contact dermatitis after prolonged contact.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

**PORTLAND CEMENT**

Portland cement clinker caused a mix of heterogeneous effects on the cornea and the calculated irritation index was 128.  
Direct contact with the cement can cause corneal lesions due to mechanical stress, immediate or delayed irritation or inflammation.  
Direct contact with large quantities of dry concrete or splashes of wet concrete can cause effects ranging from moderate eye irritation (e.g. conjunctivitis or blepharitis) to chemical burns and blindness.

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization

**PORTLAND CEMENT**

Some individuals may develop eczema following exposure to wet concrete dust, caused by an immunological reaction to water-soluble Cr(VI) that causes allergic contact dermatitis.  
The response can appear in a variety of forms that can range from a mild rash to severe dermatitis.  
No sensitizing effect is expected if the cement contains a water-soluble Cr(VI) reducing agent until the indicated period of effectiveness of such reducing agent is exceeded

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

Target organs

**PORTLAND CEMENT**

Cement dust can irritate the throat and respiratory system. Coughing, sneezing and shortness of breath may occur following exposures above the occupational exposure limits.

STOT - REPEATED EXPOSURE

May cause damage to organs

Target organs

**PORTLAND CEMENT**

Long-term exposure to respirable cement dust above the occupational exposure limit can lead to coughing, shortness of breath and chronic obstructive changes in the respiratory tract. No chronic effects were observed at low concentrations. Based on available

## SECTION 11. Toxicological information ... / >>

data, the classification criteria are not met.

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

FLUE DUST  
EC50 - for Algae / Aquatic Plants > 22,4 mg/l/72h

### 12.2. Persistence and degradability

Information not available

### 12.3. Bioaccumulative potential

Information not available

### 12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## SECTION 14. Transport information ... / >>

### 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

### 14.3. Transport hazard class(es)

not applicable

### 14.4. Packing group

not applicable

### 14.5. Environmental hazards

not applicable

### 14.6. Special precautions for user

not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006  
None

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)  
On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)  
None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:  
None

Substances subject to the Rotterdam Convention:  
None

Substances subject to the Stockholm Convention:  
None

Healthcare controls  
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1B</b>	Skin sensitization, category 1B
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)

**SECTION 16. Other information** ... / >>

15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 16.