

# SOLVLINE ONE

former SOLVENTE PER BETON-COLOR



## TECHNICAL FEATURES



SLOW CURING

## Description

SOLVLINE ONE is anhydrous and denatured butyl acetate indicated as a thinner and surface cleaner.

## Colour

SOLVLINE ONE is a clear, colorless liquid with a characteristic odor.

## Field of application

SOLVLINE ONE is used as:

- solvent for diluting BETON COLOR and other products for which anhydrous butyl acetate is required;
- detergent for cleaning surfaces stained due to improper and/or excessive applications of PRO-TILER FINITURA (See Technical Data Sheet).

## Advantages

- SOLVLINE ONE shows a very low water content, suitable for the dilution of polyurethane products (where applicable).

## Tool cleaning

- SOLVLINE ONE is suitable, as an alternative to ACETONE, for cleaning brushes, rollers and equipment for spraying solvent-based products.
- SOLVLINE ONE is not suitable for removing residues of turpentine-based products (wood impregnators, solvent-based waxes, etc.)

## Useful tips for laying

- The product is FLAMMABLE.
- Read the Safety Data Sheet carefully before use.

## Technical Data

| ► PRODUCT IDENTIFICATION DATA         |      | value                    |
|---------------------------------------|------|--------------------------|
| Density at 23°C, EN ISO 2811-1        | kg/L | 0,88 ± 0,02              |
| Appearance                            | -    | Clear transparent liquid |
| Odor                                  | -    | Characteristic           |
| Water content (Karl Fischer), ISO 760 | -    | < 0,1%                   |

## Product storage

# SOLVLINE ONE

- 24 months in the closed original packaging, in a dry and covered place away from direct sunlight, at a temperature between +5°C and +30°C.

## Packaging

| VARIANT | PACKAGE           | ADR | PACKAGE / PALLET | COMPONENTS | NOTES |
|---------|-------------------|-----|------------------|------------|-------|
| -       | 12 x 1L cans      | P*  | 32 boxes         |            | -     |
| -       | 4 x 5 L cans      | P*  | 18 boxes         |            | -     |
| -       | steel pail - 20 L | SI' | 33 buckets       |            | -     |

### ADR legend:

NO = NON-DANGEROUS goods

P\* = DANGEROUS goods packed in limited quantities (packed as per ADR Chapter 3.4)

SI = DANGEROUS Goods

## LEGAL NOTES

The information contained in this Technical Data Sheet is based on the knowledge and experience gained by Nord Resine up to the date of its issue and is for indicative purposes only. It does not constitute a technical specification nor does it imply the assumption of any warranty, express or implied, or liability regarding the results obtainable, which depend on multiple factors beyond the control of Nord Resine.

It is the user's responsibility to verify in advance, also through suitable tests, the suitability of the product for the intended use, compatibility with the substrate, appropriate environmental application conditions, and the execution of the installation according to workmanship standards, assuming all liability arising from the use of the product and the final result of the works.

Nord Resine reserves the right to modify, at any time and without prior notice, product characteristics, packaging, contained quantities, and this technical documentation. Nord Resine products are intended exclusively for professional use.

This Technical Data Sheet cancels and replaces previous editions. Please check the latest and most updated revision at <https://nordresine.com/en/>

## EDITION

Issue: 17.12.2025

Revision: -