



SEAL WAX

Dust protection wax



TECHNICAL FEATURES




BREATHABLE



FAST CURING



WALKABLE



CARRIAGEABLE

FIELD OF APPLICATION



INTERIORS




INT. FLOORS



IND. SHEDS

APPLICATIONS



1 PART



READY TO USE



WAX SPREADER

Description

SEAL WAX is a family of liquid preparations based on polymeric waxes, modifiers, additives and water for the dust protection of concrete and for final treatments in the technology of "Béton Ciré" and polymer-cement.

SEAL WAX is available in two versions:

- SEAL WAX L: double-cross-linked glossy metallic wax.
- SEAL WAX MAT: matt satin metallic wax with double crosslinking.

The product, applied on an industrial flooring, penetrates and consolidates the friable particles.

The action is completed by a thin transparent surface film that facilitates cleaning operations.

Due to its characteristics, SEAL WAX does not allow the adhesion of dirt and facilitates its removal.

Field of application

SEAL WAX est idéal pour le traitement étanche à la poussière des sols industriels en béton, colorés et naturels, et pour les traitements finaux dans la technologie du « Béton Ciré » et du polymère-ciment.

SEAL WAX allows a simple and inexpensive intervention.

Product application

► On new flooring

- Remove dust and any encrustations resulting from the cutting of the joints with a single water wash;
- Then apply SEAL WAX with a special spreader, in two coats spaced a few hours apart, taking care to cross your hands.

► On old pavement

- Degrease with STRIPPER and rinse;
- After one day of drying, apply SEAL WAX as previously described.

Consumption

type of application	minimum consumption	maximum consumption	u.m.	notes
In two hands, with spreader	0,050	0,075	L/m ²	(1)

(1) Yield = (13-20) m²/L

Tool cleaning

- Fresh product: cleaning with water (also hydrowashing).
- Hardened product: mechanical removal.

Useful tips for laying

- Do not dilute. Dilution impairs the proper formation of the wax film.

SEAL WAX

- Removing SEAL WAX requires a specific wax remover:
- STRIPPER to remove SEAL WAX N.
- STRIPPER PLUS to remove SEAL WAX L or SEAL WAX MAT.
- Read the Safety Data Sheet before use.

Technical Data

► PRODUCT IDENTIFIERS: SEAL WAX N		value
Appearance	-	White emulsion
Density at 20°C, EN ISO 2811-1	kg/L	1,04 ± 0,02
pH (potentiometric method) at 23°C, ISO 4316	-	8,4 ± 0,2
Non-volatile matter, ISO 1625	-	(20 ± 2) %
Set to foot traffic (at +23°C)	Hours	48
Minimum commissioning time (at 23°C, 50% RH)	days	7
Minimum Film Temperature (MFFT), ISO 2115	°C	+8

► PRODUCT IDENTIFICATION DATA: SEAL WAX MAT		value
Appearance	-	White emulsion
Density at 20°C, EN ISO 2811-1	kg/L	1,03 ± 0,02
pH (potentiometric method) at 23°C, ISO 4316	-	8,4 ± 0,2
Non-volatile matter, ISO 1625	-	(20 ± 2) %
Set to foot traffic (at +23°C)	Hours	48
Minimum commissioning time (at 23°C, 50% RH)	days	7
Minimum Film Temperature (MFFT), ISO 2115	°C	+8

Product storage

- 12 months in the original closed packaging, in a dry, covered environment, protected from sunlight and at a temperature between +15°C and +35°C.
- Protect the product against frost.

Packaging

VARIANT	PACKAGE	ADR	PACKAGE / PALLET	COMPONENTS	NOTES
GLOSSY	12 x 1 L bottles	NO	30 boxes		(1)
GLOSSY	4 x 5 L jerry cans	NO	24 boxes		(1)
GLOSSY	20 L - jerry can	NO	24 jerry cans		(1)
OPAQUE	4 x 5 L jerry cans	NO	24 boxes		(2)

NOTES:

(1) Metallic wax in glossy version.

(2) Metallic wax in matt version.

ADR legend:

NO = NON-DANGEROUS goods

P* = DANGEROUS goods packed in limited quantities (packed as per ADR Chapter 3.4)

SI = DANGEROUS Goods

LEGAL NOTES

Any advice concerning the methods of use of our products reflects the current state of knowledge and does not imply any guarantee and/or responsibility as to the outcome of the application. Consequently, the customer must verify the product's suitability for the intended use and purposes by testing the product in advance. The Internet website www.nordresine.com contains the latest revision of this technical sheet: in case of any doubts, verify the date of revision (where missing, use the date of issue) by consulting the "PRODUCTS" section.

SEAL WAX

EDITION

Issue: 09.01.2015

Revision: 26.01.2026